

Spec: LED PAR56 30-75V With dot cover

序号	SPEC	VOLTAGE	Current	Wattage	CBCP	H	V	distribution (cd)								备注
		V	A	W		cd			L 15°	R 15°	U 15°	D 15°	L 40°	R 40°	U 40°	
1	30-75V LED	30.0	0.85	25.5	224750	6.8	7.6	3050	2585	919	937	126	123	324	263	
2		30.0	0.85	25.5	201250	7.2	8.0	2508	2650	986	905	76	91	237	221	
3		30.0	0.83	24.9	224500	6.8	7.2	3405	1778	811	823	124	98	263	294	
4		30.0	0.83	24.9	239250	6.8	7.2	3715	2074	873	935	106	93	236	263	
5		30.0	0.86	25.8	221750	6.8	7.2	3240	2219	887	795	109	99	297	267	
	MIN	/	0.83	24.90	201250			2508	1778	811	795	76	91	236	221	
	MAX	/	0.85	25.50	224750			3050	2585	919	937	126	123	324	263	
	AVG	/	0.85	25.50	224750			3050	2585	919	937	126	123	324	263	
1	30-75V LED	75.0	0.34	25.5	218750	6.8	7.6	3060	2454	866	850	105	99	307	257	
2		75.0	0.33	24.8	193250	7.2	8.0	2470	2425	897	889	83	98	227	228	
3		75.0	0.33	24.8	221500	6.8	7.2	3200	2050	830	778	110	93	258	290	
4		75.0	0.33	24.8	231500	6.8	7.2	3575	1930	866	878	103	88	220	263	
5		75.0	0.34	25.5	213500	6.8	7.2	3075	2337	858	802	102	96	285	262	
	MIN	/	0.34	24.75	193250			2470	1930	830	778	83	88	220	228	
	MAX	/	0.34	25.50	218750			3060	2454	866	850	105	99	307	257	
	AVG	/	0.34	25.50	218750			3060	2454	866	850	105	99	307	257	

测试员: 许玲丽

日期: 2021.07.23