



**Product Number:** 64915

**Order Abbreviation:** MC150/U/ET23.5/942

**General Description:** METALARC POWERBALL 150W ceramic arc tube, 4200K, 93 CRI, reduced color shift, high performance, clear, pulse start, ET23.5, clear, enclosed rated, E 39 Mogul base.

### Product Information

Abbrev. With Packaging Info.	MC150UET235942 20/CS 1/SKU
ANSI Code	C102/E
ANSI Code 2	C102/E
Approx. Lumens (initial - horizontal)	15000
Approx. Lumens (initial - vertical)	15000
Approx. Lumens (mean - vertical)	10500
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Average Rated Life - Vertical (hr)	24000
Base	E39 Mogul
Bulb	ET23.5
Color Rendering Index (CRI)	93
Color Temperature/CCCT (K)	4200
Diameter (in)	2.953
Diameter (mm)	75.00
Family Brand Name	Metalarc® Powerball
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	410
Maximum Bulb Temperature - Fahrenheit	752
Nominal Wattage (W)	150.00
Warm-up Time (min)	2-4

### Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.